

CIRNEDOL 32



DESCRIPTION

Fluid, pale yellow oil with mild odour.

APPLICATIONS

Needle lubricant for high speed anti-hose knitting machines.

APPLICATION DETAILS

Compatible with the automatic lubricating systems fitted to most anti-hose knitting machines. It is recommended that the machine manufacturers' guidelines are followed with regard to the oil application rates.

PERFORMANCE DATA

- Provides a high standard of machine lubrication and anti-wear performance. Incorporates anti-wear and anti-corrosion additive systems.
- Has excellent stability and resistance to oxidation even when used at high machine operating temperatures.
- Formulated to minimise oil splashing and misting from knitting machines, caused by mechanical action.
- Non-corrosive to the metals normally used for textile machinery.
- Not specifically self-emulsifiable in water, but would normally be readily removed during anti-hose scouring procedures.

NOTES

When introducing a new oil to a machine we recommend cleaning the original oil from the machine and oiler unit as thoroughly as possible, to avoid the potential of any incompatibility problems.

TYPICAL CHARACTERISTICS AND PROPERTIES

CIRNEDOL 32	UNITS	TYPICAL RESULT
Viscosity @ 40°C	cSt	Approx. 32
Density @ 15°C	kg/l	Approx. 0.843
Cloud Point	°C	< 0
Flash Point (SETA)	°C	> 170
Shelf Life		7 years in original container stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other application.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: techserv@vickers-oil.com

Accredited to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717