

THROWOL B MOD



Textiles

DESCRIPTION

Clear yellow oil of mild odour. Self emulsifiable in water.

APPLICATIONS

A soaking oil for raw silk, particularly for use where traditional soaking methods are practised depending on the end use of the silk.

APPLICATION DETAILS

Weaving yarns	-	4% oil calculated on the dry weight of the silk
Knitting yarns	-	up to 16% on the weight of the fibre

An emulsion of the required concentration should be prepared by stirring the oil into water at normal room temperature. (Adding the water to the oil is not recommended). A homogenous white emulsion should be formed and the silk hanks soaked in the emulsion. Where soaking is carried out in machinery designed to circulate the liquor, for example the Franklin soaking machine, soaking is usually complete in 2 to 3 hours, or alternatively where there is no liquor circulation, the silk should be soaked for 12 hours or overnight. The temperature during soaking should not exceed 40°C (100°F). An exhaustion level of 60% to 70% can be expected.

PERFORMANCE DATA

- Softens the natural silk gum making the silk pliable for subsequent processing. It also lubricates the fibre.
- Achieves even penetration, and therefore softness, throughout the silk hanks.
- Does not require the use of additional alkalis in the soaking solution.
- Readily forms stable emulsions at dilute concentrations.
- If required, THROWOL B MOD can be removed prior to the de-gumming process by the use of a mild detergent solution.

TYPICAL CHARACTERISTICS AND PROPERTIES

THROWOL B MOD	UNITS	TYPICAL RESULT
Viscosity @ 21°C	cSt	Approx. 125
Density @ 15°C	kg/l	Approx. 0.91
Cloud Point	°C	< 0
Flash Point (SETA)	°C	> 170
Ionic Character		Non-ionic / Anionic
Active Content	%	100
Shelf Life		7 years in sealed container stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other application.

BENJ^m R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: techserv@vickers-oil.com

Accredited to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717