

H.S.T.N: 34031910 REF: MKT.PDS.104

REV: 5

VICKERLUBE BIO CPF



PART NUMBER

35283

DESCRIPTION

VICKERLUBE BIO CPF is a high-performance, readily biodegradable, multipurpose fluid made from bio-based, sustainable ingredients - designed to penetrate, lubricate, displace moisture, as well as clean and protect against corrosion. It delivers maximum performance across a wide range of applications. For use on pins, bushes, screw, valves, chains, bearings, couplings, levers, locks, hinges, cables, pulleys, winches, pedal crank arms, derailleur assemblies, gear mechanisms, and many more.

APPLICATIONS

- Automotive maintenance
- Engineering & industry
- Agricultural machinery
- Home & garden
- Mining & quarries
- Hobbies & crafts

- Bike/motorbike maintenance
- Fishing tackle and equipment
- Snow moving equipment
- Marine & offshore
- Construction
- Plant, equipment & tools
- Boating & water sports
- Printing equipment & machinery
- Garage & workshop
- Utilities maintenance
- Motor homes/caravans

METHOD OF APPLICATION

- Protect eyes, skin and do not inhale. Refer to Safety Data Sheet.
- DO NOT use on energised equipment.
- Shake well before use.
- Spray a light, even coat to protect surfaces and seal out moisture.
- Apply liberally to loosen rusted/seized parts; full penetration may require several hours.
- To displace water, spray wet surfaces until run-off is clear.
- Can be removed with VICKERLUBE CLEANER SPRAY.

Tel:


Fax:

Web:

Email:

COMPATIBILITY

VICKERLUBE BIO CPF is suitable for use on metal surfaces. Compatibility testing is recommended prior to use for all non-metal and/or coated surfaces. Store at room temperature and not in direct sunlight. Containers should be kept closed and users should consult the material safety data sheet before use.





H.S.T.N: 34031910 REF: MKT.PDS.104

REV: 5

VICKERLUBE BIO CPF



FEATURES AND BENEFITS

- Readily Biodegradable
- Market leading penetration
- Creates a thin, colourless soft coating
- · Gets under dirt, grime and grease
- Forms a soft protective layer
- · Quickly displaces water

Reduced environmental impact in the event of spillage Quickly loosens and releases metal parts and mechanical equipment that are stuck, seized or rusted together Keeps parts loose and free from corrosion

Allows easier cleaning

Provides protection against rust and corrosion

Assists in drying out equipment

HANDLING

Trigger Spray / Refill Containers

Keep out of reach of children. Read label before use. Keep away from eyes. If product gets into eyes, rinse thoroughly with water. If medical advice is needed, have product container or label at hand.

TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE BIO CPF	RESULT
Appearance	Green solution
Viscosity @ 25°C (cSt)	11
Water Solubility (g/l)	<1
Flash Point (°C)	176
Dry Film Thickness (μm)	<1
Coverage (m²/l)	330
Specific Gravity (g/cm³)	0.89
Shelf Life	3 years in original sealed containers whilst stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJ^N R. VICKERS & SONS LTD.

Registered Office

6 Clarence Road, Leeds, LS10 1ND, United Kingdom

Registered in England Company No. 00130013 Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Certified to the ISO 9001 Quality Standard and the ISO 14001 Environmental Management Standard

