

# VICKERLUBE CPVI



## PART NUMBER

35278

## DESCRIPTION

VICKERLUBE CPVI is a high performance, mineral based, corrosion preventive fluid that provides superior rust and corrosion prevention for components that will be placed into storage for extended periods of time. It fills any closed spaces with vapours to prevent rust and corrosion of surfaces not contacted by the fluid.

## APPLICATIONS

Provides internal protection of components including engines, gear boxes and other closed systems for periods up to one year, or more, depending upon how well sealed the closed system is and how much temperature induced breathing of the system occurs.

## METHOD OF APPLICATION

It is recommended that the equipment to be protected is drained of oil before VICKERLUBE CPVI is added. The treat rate is 0.1% headspace so 500 ml will treat a headspace of 500 l.

## COMPATIBILITY

Compatibility testing has successfully been carried out with commonly used elastomers, paints, and copper.

## FEATURES AND BENEFITS

- Low treat rate
- Excellent long-term corrosion protection
- Cost effective
- Extended component life

### BENJ<sup>N</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom  
**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Fax:** +44 (0) 113 386 7676  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Certified to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard



# VICKERLUBE CPVI



## HANDLING

Do not store in direct sunlight. Container should be kept closed when not being used. Read label and consult Safety Data Sheet (SDS) before use.

## TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE CPVI	RESULT
Appearance	Light amber
Viscosity @ 20°C (cSt)	4
Flash Point (°C)	100
Density (g/cm <sup>3</sup> )	0.82
Shelf Life	2 years in original sealed containers whilst stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

### BENJ<sup>N</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom  
**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Fax:** +44 (0) 113 386 7676  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Certified to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard

