

VICKERLUBE FG 3HDC GREASE 2



PART NUMBER

25562

DESCRIPTION

VICKERLUBE FG 3HDC GREASE 2 is a general purpose pharmaceutical white oil based, inorganic thickened, food grade grease. It is registered to 3H for direct contact applications to act as a release agent, lubricant and corrosion protector for use in and around food, beverage and pharmaceutical processing and production areas.

APPLICATIONS

It is designed for use on equipment and machinery working in potential direct contact with food stuffs in food and other clean industries. The grease has high adhesive properties and is extremely water resistant. It is ideal for applications where water wash down is present and there is a chance of food contact such as slaughterhouses, butcheries, blades on chopping and mincing machines, canning and bottling plants.

Applications include: -

- Roller and ball bearings in direct contact applications
- Bakery loaf pans and equipment
- Slaughterhouse and abattoir equipment
- Slides and guides
- Saw blades and chopping and dicing dies
- Medical equipment

CERTIFICATION

VICKERLUBE FG 3HDC GREASE 2 is 3H Registered – 161275, for direct food contact, Halal Certified, Kosher Certified, manufactured to ISO 9001:2015 and ISO 21469.

FEATURES AND BENEFITS

- | | |
|--------------------------------|---|
| • 3H Registered | Safe to use where direct food contact may occur |
| • Silica thickened | Good thermal stability |
| • Supreme corrosion protection | Increased component and lubricant life |
| • Odourless and colourless | Will not taint food |
| • Extremely adhesive | Lowers lubricant usage |

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717

VICKERLUBE FG 3HDC GREASE 2



METHOD OF APPLICATION

VICKERLUBE FG 3HDC GREASE 2 can be applied manually, with a standard pressure grease gun (via cartridge).

TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG 3HDC GREASE 2	TEST METHOD	RESULT
Appearance	Visual	Smooth Translucent Grease
Thickener		Inorganic
NLGI Grade	ASTM D217	NLGI 2
Base Oil		Pharmaceutical White Oil
Base Oil Viscosity (40°C) (cSt)	ASTM D7152	95
Dropping Point (°C)	ASTM D2265	>300
Copper Corrosion	ASTM D4048	1b
Temperature Range (°C)		-15 to 130
Shelf Life		3 years in original sealed containers whilst stored out of direct sunlight



Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other application.

BENJⁿ R. VICKERS & SONS LTD.

Registered Office
 6 Clarence Road, Leeds,
 LS10 1ND, United Kingdom

Registered in England
 Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on 

Certified to the ISO 9001
 Quality Standard and the
 ISO 14001 Environmental
 Management Standard



FM 01851 EMS 40717