

VICKERLUBE FG FLUID SERIES



PART NUMBER

20473 (ISO 15)	20592 (ISO 22)
20738 (ISO 32)	20846 (ISO 46)
20934 (ISO 68)	20346 (ISO 100)

DESCRIPTION

VICKERLUBE FG FLUIDS are a high-performance blend of food grade white oils fortified with the latest additive technology giving outstanding wear resistance and EP properties required for modern hydraulic and circulating systems. They are registered to H1 for incidental food contact for use in applications in and around food, beverage and pharmaceutical processing and production areas.

APPLICATIONS

VICKERLUBE FG FLUIDS are designed for hydraulic and circulating systems in the food and clean industries operating at wide temperature ranges. The lubricants have high resistance to wear and load normally experienced in hydraulic systems. The additive package gives enhanced corrosion protection properties and supports manufacturers requirements for HACCP and GMP programmes.

Applications include: -

- All hydraulic systems
- Low loaded oil lubricated bearings
- Valve Lubrication
- General purpose oil lubrication
- Variable speed drives requiring low viscosity oils
- Process machinery (Bottling and Canning)

CERTIFICATION

VICKERLUBE FG FLUIDS are NSF H1 Registered for incidental food contact, Halal Certified, Kosher Certified, manufactured to ISO 9001:2015 and ISO 21469 and meet the requirements of FDA 21 CFR 178.3570.

VICKERLUBE FG FLUIDS meet or exceed the requirements of ISO-L-HV (according to ISO 6743-4) and HLP (to DIN 51524-2).

NSF Registration (ISO 15) - 162114

NSF Registration (ISO 22) - 162115

NSF Registration (ISO 32) - 162116

NSF Registration (ISO 46) - 162117

NSF Registration (ISO 68) - 162118

NSF Registration (ISO 100) - 162119

BENJ^N R. VICKERS & SONS LTD.

Registered Office

6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England

Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717

VICKERLUBE FG FLUID SERIES



FEATURES AND BENEFITS

- H1 Registered
 - Excellent water resistance
 - Good air release properties
 - Excellent wear protection
 - Oxidation and corrosion inhibited
- Safe to use where incidental food contact may occur
 - Extends bearing, gears and gearbox life
 - Enhanced lubricity and elongates component life
 - Elongates gears and bearing life
 - Increases oil life & protects gearbox against corrosion

METHOD OF APPLICATION

VICKERLUBE FG FLUIDS can be poured directly from the container, or if using a drum, please ensure clean equipment is used to transfer product to the system.

TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG FLUID	TEST METHOD	15	22	32
Appearance	Visual	--- Clear Yellow Fluid ---		
Viscosity at 40°C (cSt)	ASTM D445	15	22	32
Viscosity at 100°C (cSt)	ASTM D445	4	4	5
Viscosity Index	ASTM D2270	116	108	106
Density at 15°C (g/cm ³)	ASTM D1298	0.84	0.86	0.87
Pour Point (°C)	ASTM D97	-44	-43	-42
Flash Point (°C)	ASTM D92	198	198	222
Copper Strip Corrosion 3h @ 100°C	ASTM D130	1a	1a	1a
Demulsibility (minutes)	ASTM D1401	<10	<10	<30
4 Ball Wear Scar Diameter (mm)	ASTM D4172	0.41	0.4	0.33
FZG Scuffing A/8.3/90 (FLS)	DIN 51534-2	ND	ND	12
Temperature Range (°C)	-	-30 to +140	-25 to +140	-25 to +140
Shelf Life	-	5 years in original sealed containers whilst stored out of direct sunlight		

BENJ^N R. VICKERS & SONS LTD.

Registered Office
 6 Clarence Road, Leeds,
 LS10 1ND, United Kingdom

Registered in England
 Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
 Quality Standard and the
 ISO 14001 Environmental
 Management Standard



FM 01851 EMS 40717

VICKERLUBE FG FLUID SERIES



TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG FLUID	TEST METHOD	46	68	100
Appearance	Visual	--- Clear Yellow Fluid ---		
Viscosity at 40°C (cSt)	ASTM D445	46	68	100
Viscosity at 100°C (cSt)	ASTM D445	7	9	11
Viscosity Index	ASTM D2270	106	107	105
Density at 15°C (g/cm ³)	ASTM D1298	0.87	0.87	0.88
Pour Point (°C)	ASTM D97	-20	-20	-15
Flash Point (°C)	ASTM D92	232	250	260
Copper Strip Corrosion 3h @ 100°C	ASTM D130	1a	1a	1a
Demulsibility (minutes)	ASTM D1401	<30	<30	10
4 Ball Wear Scar Diameter (mm)	ASTM D4172	0.34	0.33	0.34
FZG Scuffing A/8.3/90 (FLS)	DIN 51534-2	12	12	12
Temperature Range (°C)	-	-5 to +140	-5 to +140	-5 to +140
Shelf Life	-	5 years in original sealed containers whilst stored out of direct sunlight		



Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
 6 Clarence Road, Leeds,
 LS10 1ND, United Kingdom

Registered in England
 Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on 

Certified to the ISO 9001
 Quality Standard and the
 ISO 14001 Environmental
 Management Standard



FM 01851 EMS 40717