

H.S.T.N: 27101985 REF: MKT.PDS.115 REV: 2

VICKERLUBE FG **UNIVERSAL OIL 32** Food Grade **General Purpose**

PART NUMBER

45782

DESCRIPTION

VICKERLUBE FG UNIVERSAL OIL 32 is a premium quality, medicinal white oil registered to H1 for incidental food contact, for use in and around food, beverage, and pharmaceutical production areas.

APPLICATIONS

VICKERLUBE FG UNIVERSAL OIL 32 is designed for use in the food, beverage and pharmaceutical industries where there is a chance of incidental food contact.

It is primarily intended for wash down and short term (overnight) corrosion protection and light lubrication for food manufacturing equipment.

CERTIFICATION

VICKERLUBE FG UNIVERSAL OIL 32 is NSF H1 Registered - 162304, for incidental food contact, Halal Certified, Kosher Certified, manufactured to ISO 9001:2015 and meets the requirements of FDA 21 CFR 172.878 and 21 CFR 178.3620(a).

FEATURES AND BENEFITS

- H1 Registered
- Protects against corrosion
- Non-odour or tainting
- Safe to use where incidental food contact may occur Increased component life
- No effect on food stuff

METHOD OF APPLICATION

VICKERLUBE FG UNIVERSAL OIL 32 can be applied manually by brush, in a trigger spray or pressurised lubrication system capable of pumping an ISO VG 32 fluid.

BENJ^N R. VICKERS & SONS LTD.


Registered Office 6 Clarence Road, Leeds, LS10 1ND, United Kingdom

Registered in England Company No. 00130013

Tel: +44 (0) 113 386 7654 Web: www.vickers-oil.com inbox@vickers-oil.com Email:

Follow us on in 🗾 🕨

Certified to the ISO 9001 Quality Standard and the ISO 14001 Environmental Management Standard





H.S.T.N: 27101985 REF: MKT.PDS.115 REV: 2



TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG UNIVERSAL OIL 32	TEST METHOD	RESULT
Appearance	Visual	Clear and Bright
Density at 15°C (g/cm ³)	ASTM D4052	0.86
Viscosity @ 40°C (cSt)	ASTM D7042	32
Flash Point - COC (°C)	ASTM D92	>185
Pour Point (°C)	ASTM D7347	<-9
Shelf Life		2 years in original sealed containers

Shelf Life

2 years in original sealed containers stored out of direct sunlight



Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJ^N R. VICKERS & SONS LTD.

Registered Office 6 Clarence Road, Leeds, LS10 1ND, United Kingdom

Registered in England Company No. 00130013
 Tel:
 +44 (0) 113 386 7654

 Web:
 www.vickers-oil.com

 Email:
 inbox@vickers-oil.com

Follow us on in ⊻ 🕨

Certified to the ISO 9001 Quality Standard and the ISO 14001 Environmental Management Standard

