

VICKERLUBE SOFT COAT CPF



PART NUMBER

35450

DESCRIPTION

VICKERLUBE SOFT COAT CPF is a high-performance corrosion preventative which after drying leaves a soft waxy protective coating. It is a non-flammable, VOC-free product which is deposited with a non-aromatic solvent, having excellent water displacement properties. The coating provides excellent long-term corrosion protection for metal surfaces.

APPLICATIONS

- Automotive maintenance
- Engineering & industry
- Agricultural machinery
- Home & garden
- Mining & quarries
- Hobbies & crafts
- Bike/motorbike maintenance
- Fishing tackle and equipment
- Snow moving equipment
- Marine & offshore
- Construction
- Plant, equipment & tools
- Boating & water sports
- Printing equipment & machinery
- Garage & workshop
- Utilities maintenance
- Motor homes/caravans

METHOD OF APPLICATION

VICKERLUBE SOFT COAT CPF can be applied by brushing, spraying, wiping or dipping – the latter being the most effective at moisture displacement and delivery of a uniform coating. **Container should be shaken well before each use.**

COMPATIBILITY

VICKERLUBE SOFT COAT CPF is suitable for use on metal surfaces. Compatibility testing is recommended prior to use for all non-metal surfaces.

FEATURES AND BENEFITS

- Excellent long-term corrosion protection
- Excellent water displacement
- Non-flammable and VOC-free
- Does not crack, peel or chip (tested to 250°C)
- Easily removed with petroleum spirits or strong degreasers
- Extended component life
- Assists in drying out equipment
- Ease of use
- Extended component life
- Ease of use

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717

VICKERLUBE SOFT COAT CPF



HANDLING

Do not store in direct sunlight. Container should be kept closed when not being used. Read label and consult Safety Data Sheet (SDS) before use.

TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE SOFT COAT CPF	RESULT
Appearance	Brown solution, which dries to leave a clear film
Protection Level	Long term*
Drying Time (hours)	24*
Film Type	Soft, waxy
Water Displacing	Yes
Flash Point (°C)	> 100
Film Thickness (μ)	≤ 15
Coverage (m ² /l)	> 22
Density (g/cm ³)	0.9
Shelf Life	3 years in original sealed containers whilst stored out of direct sunlight

* Protection level, drying times and product selection depend on environmental conditions. To ensure appropriate product selection please discuss your requirements with Vickers Oils.

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom
Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard

