

# VICKERLUBE FG DRY PTFE SPRAY



## DESCRIPTION

VICKERLUBE FG DRY PTFE SPRAY is a high performance, food grade, multi-purpose, dry film lubricant and release spray. It is registered to H1 for incidental food contact for use in and around food, beverage and pharmaceutical processing and production areas.

## APPLICATIONS

VICKERLUBE FG DRY PTFE SPRAY is designed for all applications where a dry film lubricant is required in the food and other clean industries such as cosmetics and the pharmaceutical industry. It is an excellent non-stick dry film lubricant with excellent temperature resistance. It is an ideal lubricant to use where wet lubricants are not suitable or can cause stress cracking of packaging. VICKERLUBE FG DRY PTFE SPRAY will not cause stress cracking in plastics and will not pick up dust and dirt.

Applications include: -

- Slideways and chutes especially on packaged goods lines
- Chains
- Linkages, pins, cams, followers and other components
- Packaging machines
- Multipurpose light dry film lubrication
- Powder and dry foods production lines

## CERTIFICATION



VICKERLUBE FG DRY PTFE SPRAY is NSF H1 Registered for incidental food contact, manufactured to ISO 9001:2015 and meets the requirements of FDA 21 CFR 178.3570.

Registration No. 160654

## FEATURES AND BENEFITS

- |                                  |   |
|----------------------------------|---|
| • NSF H1 Registered              | Safe to use where incidental food contact may occur |
| • Light dry film lubricant       | Does not pick up dust and dirt                      |
| • Excellent wear protection      | Elongates component life                            |
| • Does not stress crack plastics | Safe on all packaging lines                         |
| • Wide temperature range         | Can be used in all temperature extremes             |

### BENJ<sup>N</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom

**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Follow us on   

Certified to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard



FM 01851 EMS 40717

# VICKERLUBE FG DRY PTFE SPRAY



## METHOD OF APPLICATION

Shake can thoroughly before use. Apply a thin even coating onto surface from approximately 15 - 30 cm (6 to 12 inches). Apply VICKERLUBE FG DRY PTFE SPRAY sparingly. Store in a cool, dry place, out of direct sunlight. Storage temperature should be below 50°C.

## TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FG DRY PTFE SPRAY	TEST METHOD	RESULT
Appearance	Visual	White dry film
Base Type	N/A	PTFE
Propellant	N/A	Hydrocarbon
Temperature Range (°C)		-50 to 260
Shelf Life		5 years in original sealed containers whilst stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

### BENJ<sup>n</sup> R. VICKERS & SONS LTD.

**Registered Office**  
6 Clarence Road, Leeds,  
LS10 1ND, United Kingdom

**Registered in England**  
Company No. 00130013

**Tel:** +44 (0) 113 386 7654  
**Web:** [www.vickers-oil.com](http://www.vickers-oil.com)  
**Email:** [inbox@vickers-oil.com](mailto:inbox@vickers-oil.com)

Follow us on   

Certified to the ISO 9001  
Quality Standard and the  
ISO 14001 Environmental  
Management Standard



FM 01851 EMS 40717